

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2008

Reviewed on 01/11/2008

## 1 Identification of substance

- **Product details**

- **Trade name:** CM 2000 - Part B

- **Article number:** 83-202544B

- **Application of the substance / the preparation**

- **Manufacturer/Supplier:**

DSSCC

4226 Kansas Avenue

Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

## 2 Composition/Data on components

- **Chemical characterization**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

95-63-6	1,2,4-trimethylbenzene	10-25%
1330-20-7	xylene	≤ 2.5%
98-82-8	cumene	≤ 1%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	≤ 1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

## 3 Hazards identification

- **Hazard description:** May cause skin and eye irritation.

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 2

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**

HEALTH	2
FIRE	2
PHYSICAL HAZARD	0

Health = \*2

Fire = 2

Reactivity = 0

USA

(Contd. on page 2)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2008

Reviewed on 01/11/2008

Trade name: CM 2000 - Part B

(Contd. of page 1)

## 4 First aid measures

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** Seek medical treatment.

## 5 Fire fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water

- **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

Mouth respiratory protective device.

## 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

- **Measures for environmental protection:** Inform respective authorities in case of seepage into water course or sewage system.

- **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

## 7 Handling and storage

- **Handling:**

- **Information for safe handling:**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

## 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2008

Reviewed on 01/11/2008

Trade name: CM 2000 - Part B

(Contd. of page 2)

· **Components with limit values that require monitoring at the workplace:**

**95-63-6 1,2,4-trimethylbenzene**

REL 125 mg/m<sup>3</sup>, 25 ppmTLV 123 mg/m<sup>3</sup>, 25 ppm

**1330-20-7 xylene**

PEL 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 655 mg/m<sup>3</sup>, 150 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppm

(o-, m-, &amp; p-isomers)

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppmLong-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

## 9 Physical and chemical properties

· **General Information**

**Form:** Liquid  
**Color:** According to product specification  
**Odor:** Characteristic

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 149°C (300°F)

· **Flash point:** > 63°C (> 145°F)

· **Ignition temperature:** 450.0°C (842°F)

· **Auto igniting:** Product is not selfigniting.

(Contd. on page 4)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2008

Reviewed on 01/11/2008

Trade name: CM 2000 - Part B

(Contd. of page 3)

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

**Lower:** 0.7 Vol %

**Upper:** 7.5 Vol %

· **Vapor pressure at 20°C (68°F):** 5.0 hPa (4 mm Hg)

· **Density at 20°C (68°F):** 0.937 g/cm<sup>3</sup>

· **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

· **Solvent content:**

**Organic solvents:** 22.1 %

· **Solids content:** 40.2 %

· **Volatile Organic Compounds:** Not determined

## 10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous products of decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6800 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

**95-63-6 1,2,4-trimethylbenzene**

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

· **Primary irritant effect:**

· **on the skin:** May cause skin irritation.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic.

## 12 Ecological information

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 5)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2008

Reviewed on 01/11/2008

Trade name: CM 2000 - Part B

(Contd. of page 4)

Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

## 13 Disposal considerations

- **Product:**
- **Recommendation:**  
Must not be disposed of as normal garbage. Do not allow product to reach sewage system.  
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

## 14 Transport information

- **DOT regulations:**
  
- **Hazard class:** 3
- **Identification number:** NA1993
- **Proper shipping name (technical name):** COMBUSTIBLE LIQUID, N.O.S (Aromatic 100)
- **Label:** Combustible liquid
- **Remarks:** Add "Marine Pollutant" to end of proper shipping name if shipping in a bulk container (>119 gallons).
- **Limited Quantity Exemption:** Limited Quantity applies for inner packages 1.3 gallons or smaller.
- **U.S. Domestic Ground Shipments:** Combustible liquids, n.o.s. (Aromatic 100), NA1993, PG III
- **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:** Not Regulated by D.O.T.
- **Emergency Response Guide (ERG) Number:** Not determine
  
- **Land transport ADR/RID (cross-border):**
- **ADR/RID class:** -
  
- **Maritime transport IMDG:**
- **IMDG Class:** -
- **Marine pollutant:** Yes
  
- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** -

## 15 Regulations

- **Sara**
- **Section 355 (extremely hazardous substances):**

75-56-9 | propylene oxide

(Contd. on page 6)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2008

Reviewed on 01/11/2008

**Trade name: CM 2000 - Part B**

(Contd. of page 5)

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

95-63-6	1,2,4-trimethylbenzene	10-25%
1330-20-7	xylene	≤2.5%
98-82-8	cumene	≤1%
100-41-4	ethylbenzene	≤1%
75-56-9	propylene oxide	≤0.01%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

64742-95-6	Solvent naphtha (petroleum), light arom.
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
1333-86-4	Carbon black
75-56-9	propylene oxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	D
98-82-8	cumene	D;CBD
100-41-4	ethylbenzene	D
75-56-9	propylene oxide	B2

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
1333-86-4	Carbon black	2B
75-56-9	propylene oxide	2B
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	3

· **NTP (National Toxicology Program)**

75-56-9	propylene oxide	R
---------	-----------------	---

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
75-56-9	propylene oxide	A3

· **MAK (German Maximum Workplace Concentration)**

1333-86-4	Carbon black	3
75-56-9	propylene oxide	2
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	3

(Contd. on page 7)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2008

Reviewed on 01/11/2008

Trade name: CM 2000 - Part B

(Contd. of page 6)

· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>	
1333-86-4	Carbon black
75-56-9	propylene oxide

· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>	
None of the ingredients is listed.	

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

T Toxic

N Dangerous for the environment

· **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), light arom.

1,2,4-trimethylbenzene

· **Risk phrases:**

45 May cause cancer.

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

53 Avoid exposure - obtain special instructions before use.

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

13 Keep away from food, drink and animal feedingstuffs.

16 Keep away from sources of ignition - No smoking.

20 When using do not eat or drink.

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

28 After contact with skin, wash immediately with plenty of soap and water.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

33 Take precautionary measures against static discharges.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

57 Use appropriate container to avoid environmental contamination.

64 If swallowed, rinse mouth with water (only if the person is conscious).

· **Special labeling of certain preparations:**

Contains epoxy constituents. See information supplied by the manufacturer.

(Contd. on page 8)

**Material Safety Data Sheet**  
*acc. to ISO/DIS 11014*

Printing date 01/11/2008

Reviewed on 01/11/2008

**Trade name: CM 2000 - Part B**

(Contd. of page 7)

- **National regulations:**
- **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

**16 Other information**

*The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing MSDS:** Environmental, Health & Safety Department
- **Contact:** Environmental, Health & Safety Manager

-USA-